

ASR1101A ASR1001A ASR1101A-D ASR1001A-D

RFID Reader



Features

- Wiegand26/34 bits RS-485 protocol
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- Red and Green LEDs
- Sensitive touch keypad with blue backlight
- Watch dog function ensure device free from halting
- Beep Buzzer and LED indicator
- Surface mounted installation



Technical Specification

Mode	ASR1101A	ASR1001A	ASR1101A-D	ASR1001A-D
------	----------	----------	------------	------------

System

Main Processor	8 Bit
----------------	-------

Read

Read Format	13.56MHz	13.56MHz	125KHz	125KHz
-------------	----------	----------	--------	--------

Read Range	6-8cm (max.)
------------	--------------

Reading time	<0.1s
--------------	-------

Function

Tamper Alarm	Yes
--------------	-----

Interface

To Controller	RS485	Wiegand26/34	RS485	Wiegand26/34
---------------	-------	--------------	-------	--------------

General

Keypad	12Keys(0-9,*,#)
--------	-----------------

Sensitive touch keypad	Blue backlight
------------------------	----------------

Beep Tone	Buzzer
-----------	--------

Power Supply	9-15VDC/100mA
--------------	---------------

Working Environment	-30°C~+60°C
---------------------	-------------

Working Humidity	≤95%
------------------	------

Dimension(W×D×H)	135mm*86mm*12mm
------------------	-----------------

Weight	0.25Kg
--------	--------

Dimensions

